DATASHEET

Name:

Type: Designed by:

SHADOWS

Pendant Light Lucie Koldova & Dan Yaffet



DESCRIPTION

The new Shadows Exterior collection is IP54 compliant for outdoor use: the hand-crafted wooden body of the interior lights has been replaced with a weather-resistant dural body. Special integrated connectors developed by Brokis make it easier to install, maintain, and clean the lights.


TECH. DESCRIPTION


The light conprises a glass shade, dural body with Brokis connector housing a GZ10 socket, and a silicone power cord with Brokis connector. The entire assembly is IP54 compliant. The light is suspended from a ceiling canopy.



CERTIFICATES







Product ID: PC1160

Product ID: PC1161

CONSTRUCTION SPECIFICATIONS


Weight:1.5 kg1.5 kgConstruction material:Glass, metalGlass, metalCord Length:2,000 mm2,000 mmMounting:CeilingCeilingEnvironment:OutdoorOutdoor


ELECTRICAL SPECIFICATIONS

230 V 230 V Input voltage [V]: 50-60 Hz 50-60 Hz Frequency [Hz]: 10 W 10 W Max. power [W]: 54 Coverage IP: 54 Socket: **GZ10 GZ10** Light source:

Energy class: A+ to B depending on light source A+ to B depending on light source







Product ID: PC1162

Product ID: PC1163

CONSTRUCTION SPECIFICATIONS

Weight:1.5 kg1.5 kgConstruction material:Glass, metalGlass, metalCord Length:2,000 mm2,000 mmMounting:CeilingCeilingEnvironment:OutdoorOutdoor

ELECTRICAL SPECIFICATIONS

Input voltage [V]: 230 V 230 V Frequency [Hz]: 50-60 Hz 50-60 Hz Max. power [W]: 10 W 10 W Coverage IP: 54 54 Socket: GZ10 GZ10 Light source:

Energy class: A+ to B depending on light source A+ to B depending on light source

LED SOURCE

Socket GU10 LED Type Lamp wattage [W] 6.5 W 220-240 VAC Input voltage [V] Energy class A+ Flux [lm] 336 lm Light colour [K] 2700K CRI 90+ Lifespan [h] 25,000 hr

Dimmable yes
Dimensions hxw [mm] 55 x 50 mm



Product ID: CM9963



PRODUCT OPTIONS

Glass Colour

Transparent glass	CGC23
Smoke grey - transparent glass	CGC516
Smoke brown - transparent glass	CGC538
Opaline - transparent glass	CGC38
Triplex opal	CGC39
Black - transparent glass	CGC602
Pearl grey - opaline glass	CGC1916

Glass Surface

Glossy Finish	CGSU66
Acid-etched outisde surface	CGSU67

Body Finishes

Silver anodized	CCS1917
Black anodized	CCS1948

Canopy Finishes

Brushed stainless steel	CCSC974
-------------------------	---------

Connection method

rokis connector	CCM1019	
-----------------	---------	--

Cable Colour

Silicone cable - black	CECL2758
Silicone cable - white	CECL2757

LED Source

230V, LED, GU10, 6.5W, 2700K, DIM	CER0761
230 V, LLD, GOIO, 0.3 W, 2700N, DII*I	CLD2/01

