## Guise

Design by Stefan Diez.



Reference

2271.

Application

Pendants

Installation type

Surface mounted

Description

Vibia presents a pendant lamp with two glass pieces where the light source is invisible, emanating directly from the material.

Diffuser

Borosilicate glass diffuser

Materials

Profile: Aluminum Diffuser: Borosilicate glass

Finishes



2271-18 Graphite (ADAPTA RF 9913 WX)

Sketch



**Electrical characteristics** 

1 x LED STRIP 24V 20W

Total 20.0 W







Light source: 3000K CRI >90 3484.8 lm 87.12 lm/W

Fixture: 1811.27 lm 35.8 lm/W

Driver included: CV - Constant Voltage 90-305V 50/60Hz

Electronic dimming: 1-10V

Remote dimming: DALI or Lutron ECO

**Technical characteristics** 

- The glass is made of borosilicate. It is typical for the glass to have small air bubbles, some inclusions and tiny scratches. These do not affect the quality or the resistance of the glass.

Installation and assembly

Please see the installation manual

**Light distribution** 

## **General lighting**

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency: 100% Isolux: Isolux (Floor) Coordinate system : CG Light position : X=0.00ft Y=0.00ft Z=8.20ft Total flux: 1811.27 lm

Maximum value : 195.12 cd/klm Light position : C=15.00 G=35.00 Symmetry on the planes : Double symmetrical

Certificates











