

DATASHEET

Name:
Type:
Designed by:

KNOT
Pendant Light
Chiaramonte Marin



DESCRIPTION


Knot is a collection of stately pendent lights that appose two dramatically dissimilar materials. The design combines coarse natural fibre with smooth, transparent handblown glass to arouse a contrast a sstriking as it is dignified.

TECH. DESCRIPTION

The light comprises a glass shade, leather suspension straps, and tubular LED module with triplex opal glass diffusor. The LED module uses a Brokis connector. The entire assembly is secured with dural endcaps. The light is hung from a ceiling canopy, which also houses the electronics and terminal connectors.




CERTIFICATES



Product ID: PC1016

Knot Sfera

12 kg
Glass, metal, linen rope
Individual, max. 5,000 mm
Ceiling
Indoor



Product ID: PC1017

Knot Disco

12 kg
Glass, metal, linen rope
Individual, max. 5,000 mm
Ceiling
Indoor


CONSTRUCTION SPECIFICATIONS

Weight:
Construction material:
Cord Length:
Mounting:
Environment:

ELECTRICAL SPECIFICATIONS

Input voltage [V]: 100 - 240 V
Frequency [Hz]: 50-60 Hz
Max. power [W]: 15 W
Coverage IP: 20
Socket: LED module
Light source: -
Energy class: A+


100 - 240 V
50-60 Hz
15 W
20
LED module
-
A+



Product ID: PC1018

Knot UOVO

7 kg
 Glass, metal, linen
 Individual, max. 5,000 mm
 Ceiling
 Indoor



Product ID: PC1019

Knot Cilindrop

7 kg
 Glass, metal, linen
 Individual, max. 5,000 mm
 Ceiling
 Indoor

CONSTRUCTION SPECIFICATIONS

Weight:
 Construction material:
 Cord Length:
 Mounting:
 Environment:

ELECTRICAL SPECIFICATIONS

Input voltage [V]: 100 - 240 V
 Frequency [Hz]: 50-60 Hz
 Max. power [W]: 15 W
 Coverage IP: 20
 Socket: LED module
 Light source: -
 Energy class: A+

100 - 240 V
 50-60 Hz
 15 W
 20
 LED module
 -
 A+

LED SOURCE

Type: LED module
 Lamp wattage [W]: 14 W
 Input voltage [V]: 24 VDC
 Energy class: A+
 Flux [lm]: 1816 lm
 Light colour [K]: 2700K
 CRI: 80+
 Lifespan [h]: 20,000 hr
 Dimmable: yes




Product ID: CM4015

CEILING CANOPY


Dimensions \varnothing x w [in/mm] 8" x 2.35" / 202 x 60 mm

Weight [kg] 1.15 kg


Material metal



Drawing



Canopy bracket



PRODUCT DETAILS

Glass Colour

| | |
|---------------------------------|--------|
| Transparent glass | CGC23 |
| Smoke grey - transparent glass | CGC516 |
| Smoke brown - transparent glass | CGC538 |
| Opaline - transparent glass | CGC38 |

Glass Surface

| | |
|--------------------------|---------|
| Glossy finish | CGSU66 |
| Matte inner glass finish | CGSU880 |

Body Finishes

| | |
|---|---------|
| Copper | CCS584 |
| Brass | CCS69 |
| Chrome black | CCS959 |
| Brushed stainless steel | CCS68 |
| Black matte powder coating with structure | CCS2673 |

Canopy Finishes

| | |
|---|----------|
| Copper | CCSC896 |
| Brass | CCSC897 |
| Chrome black | CCSC975 |
| Brushed stainless steel | CCSC974 |
| Black matte powder coating with structure | CCSC2674 |

Rope

| | |
|----------------|--------|
| Rope - natural | CRP970 |
|----------------|--------|

LED Source

| | |
|--|---------|
| 24V, LED, 14W, 2700K, 1660lm, RA80+, DIM | LEDS982 |
|--|---------|

Dimmable version

| | |
|------------------------------------|----------|
| Non-dimmable version | CEDV1457 |
| RF system - remote control version | CEDV1461 |
| PWM Single | CEDV1459 |
| 1-10V | CEDV1460 |
| DALI version | CEDV1458 |
| AC phase-out | CEDV1730 |