



## Description

The concept of a line of light is rooted in the varying characteristics of the material and its forms. The design employs the effect of light uniformly dispersed over a sandblasted surface, which in profile creates the impression of a luminous line.

## Tech. description

The light consists of a glass base with lead cable, glass diffuser, and GZ10 light source socket. The glass shade rests atop the base.




Colours options: [https://brokis.sharepoint.com/:b/s/brokis\\_sp/EboKw3iXMtREkH-l8WjXJH0BQ73NifiYVE6ITYv4N6IOvw](https://brokis.sharepoint.com/:b/s/brokis_sp/EboKw3iXMtREkH-l8WjXJH0BQ73NifiYVE6ITYv4N6IOvw)

## CONSTRUCTION SPECIFICATION

<b>Weight:</b>	3 kg
<b>Construction material:</b>	glass, metal
<b>Cord length [mm]:</b>	2,250 mm
<b>Mounting:</b>	Table
<b>Environment:</b>	Indoor

## DIMENSIONS [mm]



## ELECTRICAL SPECIFICATION

<b>Input voltage [V]:</b>	230 V
<b>Frequency [Hz]:</b>	50-60 Hz
<b>Max. power [W]:</b>	10 W LED
<b>Coverage IP:</b>	20
<b>Socket:</b>	GZ10
<b>Light source:</b>	-
<b>Energy class:</b>	A+ to E depending on light source

## CERTIFICATIONS





### CM3037

<b>Socket</b>	GU10
<b>Type</b>	LED
<b>Lamp wattage [W]</b>	5 W
<b>Input voltage [V]</b>	220 - 240 VAC
<b>Energy class</b>	A+
<b>Flux [lm]</b>	336 lm
<b>Light colour [K]</b>	2700 K
<b>CRI</b>	90+
<b>Lifespan [h]</b>	25000h
<b>Dimmable</b>	yes
<b>Dimensions h x w [mm]</b>	55 x 50 mm