# Kontorno



All of our products come with a two year standard warranty. Check US & Canada Term and Condition sales@vibia.com

### 6414

Design By Sebastian Herkner

The convex shade wall light features an open metal frame embedded with LEDs that contains a reflector formed from a rounded sheet. The black frame is affixed to the wall and casts a diffused glow that evokes the look of raining light.

#### Spec sheet

	Finish	11 Black NCS S 8500-N	Lighting effect Reflected
	LED	2700 K / 3500 K	Creation of visual hierarchies within the luminaire itself, emphasising the materiality and texture of the
	Dimming	0-10V	
	Installation type	Surface	Photometric Data
	LED	CRI>90 2165 lm 104 2700 K / 3500 K	120° Angulos Gamma 100° 120° 105° 105°
1	Driver	Constant Current 750 100~277 V V 50~60 Hz HZ	20·
		↓ F/Dimmable LED IP20 Multi-volt <sup>®</sup>	15'
	Application	Wall Fixtures Box	60" 60"
	Packaging	Gross weight Net weight	45'
			30° 15° 0° 15° 30°
7 <u>3/4"</u>			
36 1/4"			
39			
ai] $ ightarrow$			Efficiency45.26 lm/WCoordination SystemCGTotal Flux1117.95 lmMaximum Value349.46 cd
Any modifications require a minimum order quantity and extra lead time			

## Kontorno

International T 732 417 1700 Spain / Portugal T +34 934 796 970

### sales@vibia.com www.vibia.com/us/usa

### 6444

Design By Sebastian Herkner

The glass shade wall light features an open metal frame imbedded with LEDs that contains a cylindrical diffuser made of handblown opaline glass. The black frame is affixed to the wall, generating a warm, 360-degree glow as if from a fire. Install in a vertical position.

### Spec sheet






Lighting effect Black NCS S 8500-N 2700 K / 3500 K Dimming 0-10V Installation type Surface CRI>90 2165 lm 104 2700 K / 3500 K Constant Current 750 100~277 V V 50~60 Hz HZ 90 Driver LED IP20 Multi-volt Us 76 Application Wall Fixtures Packaging Box Gross weight Net weight **Total Flux** Maximum Value

Volumetric Diffuser Subtly directed, diffused light that generates a soft hierarchy of light on to the illuminated surface




Photometric Data 120° Ángulos ( 180 75 15° 30



Coordination System

CG 1034.74 lm 171.64 cd

All of our products come with a two year standard warranty. Check US & Canada Term and Condition sales@vibia.com



 $(\mathbb{D})$ 

Ø 6'

Any modifications require a minimum order quantity and extra lead time



International T 732 417 1700 Spain / Portugal T +34 934 796 970

