

Musa

Design by Note Design Studio.

VIBIA

Reference

7415.

Application

Wall Fixtures

Installation type

Surface mounted

Description

Musa, made from an aluminum base with a triple blown-glass opal diffuser, combines delicacy and subtlety. The base captures light as the small glass sphere transforms it into a soft illumination. The wall lamp remains cool to the touch thanks to an innovative heat dissipation system.

Diffuser

Blown-glass diffuser

Materials

Diffuser: Blown-glass

Body: Aluminum

Wall plate: Steel

Finishes



7415-58 Matt salmon (NCS S 1010-Y50R)




7415-59 Mink (NCS S 2005-Y50R)



7415-93 White (RAL 9016)

Sketch



Light source: 2700K CRI >90 449 lm 99 lm/W

Fixture: 356 lm 79 lm/W

Driver included: CC - Constant Current 350 mA 120V 50/60Hz

Electronic dimming: TRIAC


Installation and assembly

Please see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Coordinate system : CG

Isolux : Isolux (Floor)

Maximum value : 82.62 cd/km

Light position :

Light position : C=285.00 G=25.00

X=0.00m Y=0.00m Z=2.50m

Symmetry on the planes : Symmetrical planes

270-90

Certificates



Electrical characteristics

1 x LED 4.5W 350mA

Total 4.5 W

