

North

Design by Arik Levy.

VIBIA

Reference

5666.

Application

Floor Lamps

Installation type

Surface mounted

Description

North floor-pendant is recognized for its reinvention of the floor and pendant light category. Light is allowed where it's required from the counterweight placed on the ground that guides the electrical steel cable and suspended rod to any angle.

Diffuser

Acrylic diffuser

Materials

Cane: Carbon fiber

Shade: Aluminum

Canopy: Steel

Diffuser: Acrylic

Finishes



5666-10 White (NCS S 0300-N)




5666-11 Black (NCS S 8500N)



5666-24 Cream (NCS S 2005-Y50R)

Sketch



Electrical characteristics

1 x LED 9W 350mA

Total 9.0 W



Light source: 2700K CRI >80 1041 lm 116 lm/W

Fixture: 766.49 lm 85.16 lm/W

Driver included: CC - Constant Current 350 mA 110~240V 50/60Hz

Electronic dimming: PUSH

Technical characteristics

- Cord and plug
- cULus Certification is only approved for 120V
- Push button on base dimming


Installation and assembly

Please see the installation manual

Light distribution

General lighting - opaque shade

Fixture suitable for general ambient illumination, distributing light mainly upward and/or downward.



Photometric data

Certificates

