Origami

Design by Ramón Esteve.



Reference

4506.

Application

Outdoor

Installation type

Surface mounted

Description

ORIGAMI blends light functionality with an opportunity for artistic creation. With the new express clusters, designers can more easily create wall sconce patterns with 2, 3, or 4 piece preset configurations. ORIGAMI is LED and requires only one power feed for each cluster, and is also rated for outdoor and wet locations. Available in white, brown, terra dark, or green lacquer finish options.

Diffuser

Polycarbonate diffuser

Materials

Shade: ABS Lid: Polycarbonate

Finishes



4506-10 White (NCS S 0300-N)



4506-29 Brown D1 (NCS S 8005-Y50R)




4506-38 Terra Dark (NCS S 5040-Y70R)



4506-53 Green M1 (NCS S 6005-G80Y)

Sketch



Electrical characteristics

3 x LED STRIP 6.3W 350mA

Total 18.9 W



Light source: 2700K CRI >80 2269 lm 120 lm/W

Fixture: 1313 lm 63 lm/W

Driver included: CC - Constant Current 350 mA 120V 50/60Hz

Electronic dimming: TRIAC

Technical characteristics

- A maximum of 30 modules can be connected to a single connection point. For bigger compositions, check connection system.

Installation and assembly

Please see the installation manual

Light distribution

Indirect lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.





