Rhythm

Reference 2152.

Application Pendants

Installation type Surface mounted

Description

Design by Arik Levy.

VIBIA





Light source: 2700K CRI >90 20760 lm 119 lm/W Driver included: CV - Constant Voltage 120~277V 50/60Hz

Electronic dimming: 1-10V

Technical characteristics

- Downlighting

- Cable can be adjusted in the field. 157" max.

Installation and assembly Please see the installation manual


Light distribution Indirect lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric data Efficiency : 54.08 lm/W Coordinate system : CG Total flux : 7813.93 lm Maximum value : 2702.92 cd Light position : C=0.00 G=180.00

Isolux : Ceiling Light position : X=0.00m Y=0.00m Z=2.50m



Certificates

Total 174.0 W





AM STUDIO LIGHTING INC. | 80 KINCORT ST. TORONTO M6M 5G1 | T. 416 783 4100 | INFO@AMSTUDIO.CA | AMSTUDIO.CA

Polycarbonate diffuser

Diffuser

Materials Stick: Polyamide 6 with 10% of Fiberglass Canopy: Steel

Finishes

2152-14 Dark chocolate matte lacquer (RAL 8019)


RHYTHM is a pendant lamp with a groundbreaking design, allowing infinite configurations

thanks to modules of vertical, short stickers with uplighting. Designed by Arik Levy, it is

available in two colors: off white lacquer or matt dark brown.

2152-58 Off-white (D2-1109005 Matt beige)

Sketch



Electrical characteristics 30 x LED STRIP 30V 5.8W

A⁺